

**ANCHORWELD 2701 SUPER CLEAR** 

Revision date 20-Dec-2023 **Revision Number** 2 Supersedes Date: 01-Dec-2022

# Section 1: Identification: Product identifier and chemical identity

Product identifier

**Product Name** ANCHORWELD 2701 SUPER CLEAR

Product Code(s)

30608606

30608606; 30608607; 30803689; 30803690

Other means of identification

**UN** proper shipping name Adhesives

**UN** number or ID number UN1133

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Adhesives

Uses advised against No information available.

Details of manufacturer or importer

Supplier

Bostik Australia Pty Ltd 51-71 High Street, Thomastown Victoria

Australia

Tel: 613 9279-9333 Fax: 613 9279-9342

ABN: 79 003 893 838

au-bostik-sds@bostik.com E-mail address

Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

# Section 2: Hazard(s) identification

#### GHS Classification

Flammable liquids	Category 2 - (H225)
Aspiration hazard	Category 1 - (H304)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Reproductive toxicity	Category 2 - (H361)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Specific target organ toxicity (repeated exposure)	Category 2 - (H373)

# Label elements

Flame

Australia - EN Page 1/13

### **ANCHORWELD 2701 SUPER CLEAR**

**Revision Number** 2

Revision date 20-Dec-2023 Supersedes Date: 01-Dec-2022

# Exclamation mark Health hazard



### Signal word DANGER

#### **Hazard statements**

H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H361 - Suspected of damaging fertility or the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

Repeated exposure may cause skin dryness or cracking

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/clothing and eye/face protection

Wash face, hands and any exposed skin thoroughly after handling

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Ground and bond container and receiving equipment

Use non-sparking tools

Take action to prevent static discharges

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Keep cool

# Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of water and soap

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash it before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or doctor

Do NOT induce vomiting

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

# **Precautionary Statements - Storage**

Store in a well-ventilated place

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Other hazards which do not result in classification

In use, may form flammable/explosive vapor-air mixture.

# Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Australia - EN Page 2 / 13

**ANCHORWELD 2701 SUPER CLEAR** 

Revision Number 2 Supersedes Date: 01-Dec-2022

Revision date 20-Dec-2023

Poison Schedule Number Not applicable

# Section 3: Composition and information on ingredients, in accordance with Schedule 8

#### Substance

Not applicable

#### <u>Mixture</u>

Chemical name	CAS No.	Weight-%
2-Methylpentane	107-83-5	30 - 60
Acetone	67-64-1	10 - <30
Toluene	108-88-3	10 - <30
Zinc oxide	1314-13-2	0 - <10
Non-hazardous ingredients	Proprietary	Balance

#### Section 4: First aid measures

**Emergency telephone number** Poisons Information Center, Australia: 13 11 26

Poisons Information Center, New Zealand: 0800 764 766

Description of first aid measures

**General advice** Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

**Inhalation** Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing

has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical attention.

Delayed pulmonary edema may occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and

persists.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Get medical attention if irritation develops and persists.

**Ingestion** Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious

person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Get immediate medical attention.

**Self-protection of the first aider** Remove all sources of ignition. Ensure that medical personnel are aware of the

material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth

resuscitation. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and

tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Note to physicians Because of the danger of aspiration, emesis or gastric lavage should not be employed

Australia - EN Page 3/13

**ANCHORWELD 2701 SUPER CLEAR** 

**Revision Number** 2 Supersedes Date: 01-Dec-2022

unless the risk is justified by the presence of additional toxic substances.

Revision date 20-Dec-2023

### Section 5: Firefighting measures

**Suitable Extinguishing Media** 

Suitable extinguishing media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media No information available.

Specific hazards arising from the chemical

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

**Hazardous combustion products** Carbon oxides. Hydrocarbons.

Special protective actions for fire-fighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

### Section 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled

material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

**Environmental precautions** 

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or **Environmental precautions** 

spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

**Methods for containment** Stop leak if you can do it without risk. Do not touch or walk through spilled material. A

> vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand

or other non-combustible material and transfer to containers for later disposal.

Take precautionary measures against static discharges. Dam up. Soak up with inert Methods for cleaning up

absorbent material. Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

# Section 7: Handling and storage, including how the chemical may be safely used

Australia - EN Page 4 / 13

**ANCHORWELD 2701 SUPER CLEAR** 

Revision Number 2 Supersedes Date: 01-Dec-2022

#### Precautions for safe handling

# Advice on safe handling

Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

Revision date 20-Dec-2023

#### General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

### Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked

up. Keep out of the reach of children. Store away from other materials.

Recommended storage

temperature

Keep at temperatures between 41 and 77 °F / 5 and 25 °C.

**Incompatible materials** Strong acids. Strong bases. Strong oxidizing agents.

### Section 8: Exposure controls and personal protection

# **Control parameters**

# **Exposure Limits**

Chemical name	Australia
Acetone	TWA: 500 ppm
67-64-1	TWA: 1185 mg/m <sup>3</sup>
	STEL: 1000 ppm
	STEL: 2375 mg/m <sup>3</sup>
Toluene	TWA: 50 ppm
108-88-3	TWA: 191 mg/m <sup>3</sup>
	STEL: 150 ppm
	STEL: 574 mg/m <sup>3</sup>
Zinc oxide	TWA: 10 mg/m <sup>3</sup>
1314-13-2	TWA: 5 mg/m <sup>3</sup>
	STEL: 10 mg/m <sup>3</sup>

OEL as published by Safe Work Australia

### **Biological occupational exposure limits**

### **Appropriate engineering controls**

**Engineering controls** Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Australia - EN Page 5/13

**ANCHORWELD 2701 SUPER CLEAR** 

Revision Number 2 Supersedes Date: 01-Dec-2022

Revision date 20-Dec-2023

**Eye/face protection** Tight sealing safety goggles.

**Skin and body protection** Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

Antistatic boots.

**Hand protection** Wear suitable gloves. Impervious gloves.

**Respiratory protection** Organic gases and vapors filter conforming to EN 14387.

**Environmental exposure controls** No information available.

# Section 9: Physical and chemical properties

#### Information on basic physical and chemical properties

Physical state Liquid Appearance Liquid

Color white to yellow Milky white

Odor Solvent

Odor threshold No information available

Property Values Remarks • Method

**pH** No data available Not applicable Insoluble in water

pH (as aqueous solution)

Melting point / freezing point

No data available

No data available

Initial boiling point and boiling > 55 °C

range

Flash point -18 °C

Evaporation rate No data available

Flammability No data available Flammable liquid

Flammability Limit in Air

Upper flammability or explosive 8.0 (Toluene)

limits

Lower flammability or explosive 1.2 (Toluene)

limits

Vapor pressure <110 kPa
Relative vapor density > 1
Relative density 0.83

Water solubilityInsoluble in waterSolubility(ies)No data availablePartition coefficientNo data available

Autoignition temperature > 200

Decomposition temperatureNo data availableKinematic viscosityNo data availableDynamic viscosity250 - 400 mPa sExplosive propertiesNo information availableOxidizing propertiesNo information available

Other information

Solid content (%) No information available Density No information available

VOC content No information available

# Section 10: Stability and reactivity

Reactivity

**Reactivity** No information available.

Chemical stability

Australia - EN Page 6/13

**ANCHORWELD 2701 SUPER CLEAR** 

Revision Number 2 Supersedes Date: 01-Dec-2022

Revision date 20-Dec-2023

**Stability** Stable under normal conditions.

**Explosion data** 

Sensitivity to mechanical None.

impact

Sensitivity to static discharge Yes.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks.

**Incompatible materials** 

**Incompatible materials** Strong acids. Strong bases. Strong oxidizing agents.

**Hazardous decomposition products** 

Hazardous decomposition

products

None known based on information supplied.

### Section 11: Toxicological information

#### **Acute toxicity**

#### Information on likely routes of exposure

#### **Product Information**

**Inhalation** Specific test data for the substance or mixture is not available. Aspiration into lungs can

produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact Specific test data for the substance or mixture is not available. May cause irritation.

Causes serious eye irritation. (based on components). May cause redness, itching, and

pain.

**Skin contact** Repeated exposure may cause skin dryness or cracking. Specific test data for the

substance or mixture is not available. Causes skin irritation. (based on components).

**Ingestion** Specific test data for the substance or mixture is not available. Potential for aspiration if

swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may

cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause

redness and tearing of the eyes. Inhalation of high vapor concentrations may cause

symptoms like headache, dizziness, tiredness, nausea and vomiting.

# Numerical measures of toxicity - Product Information

# The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) >5000 mg/kg
ATEmix (dermal) >5000 mg/kg
ATEmix (inhalation-gas) >20000
ATEmix (inhalation-vapor) >20 mg/l
ATEmix (inhalation-dust/mist) >5

Australia - EN Page 7/13

**ANCHORWELD 2701 SUPER CLEAR** 

Revision date 20-Dec-2023 **Revision Number** 2 Supersedes Date: 01-Dec-2022

# **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
2-Methylpentane	LD50 >10,000 mg/kg	-	-
Acetone	=5800 mg/kg (Rattus) 3000 mg/Kg (mouse)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Toluene	=5580 mg/kg (Rattus)	= 12000 mg/kg (Oryctolagus cuniculus)	>20 mg/L (Rattus) 4 h
Zinc oxide	>5000 mg/kg (Rattus)	LD50 >2000 mg/Kg (Rattus) (OECD 402)	LC50 (4h) >5.7 mg/l

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Component Information					
Toluene (108-88-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
Regulation (EC) No.	Rabbit	Dermal			Irritant
440/2008, Annex, B.4					

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Component Information	ı				
Acetone (67-64-1)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye			irritant
Acute Eye		_			
Irritation/Corrosion					

**Respiratory or skin sensitization** Based on available data, the classification criteria are not met.

Component Information			
Acetone (67-64-1)			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	Not a skin sensitizer
Sensitization			

Toluene (108-88-3)					
Method	Species	Exposure route	Results		
Regulation (EC) No. 440/2008,	Guinea pig		No sensitization responses		
Annex, B.6 (Maximization test)			were observed		

Germ cell mutagenicity No information available.

Component Information		
Toluene (108-88-3)		
Method	Species	Results
Regulation (EC) No. 440/2008, Annex, B.13/14	Salmonella typhimurium	Not mutagenic
(Ames test)		-
OECD Test No. 476: In vitro Mammalian Cell	Mouse	Not mutagenic
Gene Mutation Test		-

Australia - EN Page 8/13

**ANCHORWELD 2701 SUPER CLEAR** 

Revision Number 2 Supersedes Date: 01-Dec-2022

Revision date 20-Dec-2023

# Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	Australia	European Union	IARC
Toluene			Group 3
108-88-3			·

Legend

IARC (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity Classification based on data available for ingredients. Suspected of damaging fertility or

the unborn child.

Component Information					
Toluene (108-88-3)					
Method	Species	Results			
OECD 407	in vivo	Reproductive toxicant			

**STOT - single exposure** May cause drowsiness or dizziness.

**STOT - repeated exposure** May cause damage to organs through prolonged or repeated exposure.

Component Information					
Toluene (108-88-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
Regulation (EC) No. 440/2008, Annex, B.26	Rat, male, female	Oral		91 days	NOAEL: 625 mg/kg
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat, male, female	Inhalation, vapor			NOAEL: 1.131 mg/l

**Aspiration hazard** May be fatal if swallowed and enters airways.

# Section 12: Ecological information

# **Ecotoxicity**

# **Aquatic ecotoxicity**

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
2-Methylpentane	EC50 = 4.321 mg/L	-	-	LC50 = 3.649 mg/L
107-83-5	(Green algae)			(Daphnia magna)
Acetone	-	LC50 96 h 4.74 - 6.33	EC50 = 14500 mg/L 15	EC50 48 h 10294 -
67-64-1		mL/L (Oncorhynchus	min	17704 mg/L (Daphnia
		mykiss )		magna Static)
Toluene	EC50 72 h = 12.5 mg/L	LC50 96 h 5.89 - 7.81	EC50 = 19.7 mg/L 30	EC50: =11.5mg/L (48h,
108-88-3	(Pseudokirchneriella	mg/L (Oncorhynchus	min	Daphnia magna) EC50:
	subcapitata)	mykiss flow-through)		5.46 - 9.83mg/L (48h,
		LC50 96 h = 5.8 mg/L		Daphnia magna)
		(Oncorhynchus mykiss		
		semi-static)		
Zinc oxide	LC 50 (72Hr) 0.136 mg/L	LC50 (96h) =0.7 mg/L	-	LC 50 (48Hr) =0.5 mg/l
1314-13-2		(Danio rerio)		(Ceriodaphnia dubia)

Australia - EN Page 9/13

**ANCHORWELD 2701 SUPER CLEAR** 

Revision Number 2 Supersedes Date: 01-Dec-2022

Revision date 20-Dec-2023

### Persistence and degradability

Persistence and degradability No information available.

Component Information				
Acetone (67-64-1)				
Method	Exposure time	Value	Results	
OECD Test No. 301B: Ready	28 days	biodegradation	91 % Readily biodegradable	
Biodegradability: CO2 Evolution Test	-	-		
(TG 301 B)				

Zinc oxide (1314-13-2)				
Method	Exposure time	Value	Results	
			The methods for determining	
			biodegradability are not	
			applicable to inorganic	
			substances	

#### Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

# **Component Information**

Chemical name	Partition coefficient
2-Methylpentane	3.214
107-83-5	
Acetone	-0.24
67-64-1	
Toluene	3.93
108-88-3	

# **Mobility**

Mobility in soilNo information available.MobilityNo information available.

Other adverse effects

Other adverse effects No information available.

# Section 13: Disposal considerations

# **Disposal methods**

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or

weld containers.

# Section 14: Transport information

# **ADG**

Australia - EN Page 10 / 13

**ANCHORWELD 2701 SUPER CLEAR** 

**Revision Number** 2 Supersedes Date: 01-Dec-2022

Revision date 20-Dec-2023

UN1133 **UN number or ID number UN proper shipping name** Adhesives

Transport hazard class(es) Packing group Ш **Environmental hazard** Yes Limited quantity (LQ) 5 L

Description UN1133, Adhesives, 3, II

Hazchem code •3YE

IATA

**UN** number or ID number UN1133 Transport hazard class(es) Ш Packing group **ERG Code** 3L **Special Provisions** АЗ Limited quantity (LQ)

UN1133, Adhesives, 3, II Description

Not regulated **UN** number or ID number UN1133 Transport hazard class(es) 3 Packing group Ш F-E, S-D EmS-No.

**Limited Quantity (LQ)** 5 L Marine pollutant

Description UN1133, Adhesives (2-Methylpentane), 3, II, (-18°C c.c.), Marine pollutant

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

# Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **National regulations**

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

**Poison Schedule Number** Not applicable

#### **Illicit Drug Precursors/Reagents**

This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list.

# Major hazard (accident/incident planning) regulation

Verify that license requirements are met

Threshold quantity (T) Hazardous chemical Liquids that meet the criteria for Class 3 Packing Group II or III 50 000 Liquids with flash points <61°C kept above their boiling points 200

at ambient conditions

National pollutant inventory

Subject to reporting requirement

Australia - EN Page 11/13

#### **ANCHORWELD 2701 SUPER CLEAR**

Revision Number 2 Supersedes Date: 01-Dec-2022

Revision date 20-Dec-2023

Chemical name	National pollutant inventory	
2-Methylpentane	20 MW Threshold category 2b total	
107-83-5	60000 MWH Threshold category 2b total	
	1 tonne/h Threshold category 2a total	
	25 tonne/yr Threshold category 1a total	
	400 tonne/yr Threshold category 2a total	
	2000 tonne/yr Threshold category 2b total	
Acetone	e 10 tonne/yr Threshold category 1	
67-64-1		
Toluene	10 tonne/yr Threshold category 1	
108-88-3		
Zinc oxide	10 tonne/yr Threshold category 1	
1314-13-2		

# **International Inventories**

AIIC Listed
NZIOC Not Listed
ENCS Not Listed
IECSC Not Listed
KECL Not Listed
PICCS Not Listed

#### Legend:

**AllC** - Australian Inventory of Industrial Chemicals **NZIoC** - New Zealand Inventory of Chemicals

ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

# **International Regulations**

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

#### Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

### **SVHC: Substances of Very High Concern for Authorization:**

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

### 2015/863/EU - RoHS

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

### Section 16: Any other relevant information

Prepared By Product Safety & Regulatory Affairs

Revision date 20-Dec-2023

Australia - EN Page 12/13

#### **ANCHORWELD 2701 SUPER CLEAR**

Revision date 20-Dec-2023 **Revision Number** 2 Supersedes Date: 01-Dec-2022

### **Revision Note**

\*\*\*Indicates updated data since last publication.

### Key or legend to abbreviations and acronyms used in the safety data sheet

### Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value Sk\* Skin designation

Carcinogen С

**Section 11: TOXICOLOGICAL INFORMATION** 

LD50 (lethal dose)

Section 12: Ecological information EC50 (effective concentration)

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet** 

Australia - EN Page 13/13